



PREMIUM GRADE

Full Mortise Cabinet Butt Hinges

Five Knuckle, Plain Bearing with Ball Tip

Free Floating Stainless Steel Pin System. Template Hole Location for All Applications. Universal Handing. Regularly Furnished with No. 8 \times 1" FHWS. Solid Extruded Brass. Solid Brass Bearing. Standard, Custom Plated and Patinated Finishes Available.

Full Scale

FINE ARCHITECTURAL, BUILDERS' AND CABINETMAKERS' HARDWARE

FULL MORTISE BUTT HINGES (CABINET)

PLAIN BEARING (Ball Tip Finial Standard)

Hinge Dimension (Height by Width)	Barrel Diameter	Leaf Thickness	Screw (FHWS)
1 ½ × 1 ½	5/16	0.083	No.6 \times $\frac{3}{4}$
2 × I ½	5/16	0.083	No. 6 \times $\frac{3}{4}$
2 × I ³ / ₄	5/16	0.089	No. 6 \times $\frac{3}{4}$
2 × 2	5/16	0.089	No.6 \times $\frac{3}{4}$
$2\frac{1}{2} \times 1^{3/4}$	5/16	0.089	No.6 \times $\frac{3}{4}$
$2\frac{1}{2} \times 2$	5/16	0.089	No. 6 \times $\frac{3}{4}$
$2\frac{1}{2} \times 2\frac{1}{2}$	5/16	0.092	No. 6 \times $\frac{3}{4}$
3 × 2	5/16	0.089	No. 8 \times $\frac{3}{4}$
$3 \times 2^{1/2}$	5/16	0.092	No. 8 × 3/4